## International Journal of Agriculture and Nutrition

ISSN Print: 2664-6064 ISSN Online: 2664-6072 IJAN 2023; 5(2): 11-15 www.agriculturejournal.net Received: 19-05-2023 Accepted: 22-06-2023

#### Ahmed AU Farah

Department of Agricultural Engineering, Faculty of Agriculture University of Gezira, Wad Medani, Sudan

#### Abdihamid SH Abdi

Department of Agricultural Engineering, Faculty of Agriculture University of Gezira, Wad Medani, Sudan

Corresponding Author: Ahmed AU Farah Department of Agricultural Engineering, Faculty of Agriculture University of Gezira, Wad Medani, Sudan

## Evaluation of hydraulic performance of three different emitters in drip irrigation systems for small vegetable farms, Gezira state, Sudan

## Ahmed AU Farah and Abdihamid SH Abdi

## DOI: https://doi.org/10.33545/26646064.2023.v5.i2a.123

#### Abstract

Drip irrigation system is the most efficient economical method for irrigation vegetable production. The objective of this study was to evaluate the hydraulic performance of three different types of emitter's namely Regular gauge (RG), Compensating pressure (CP) and non-Compensating pressure (NCP) using eggplant (Solanum melonga L.) as a test of a crop. The experiment was conducted in a Faculty of Agricultural Science, University of Gezira during the period of October 2021 to march 2022. Parameters of hydraulic performance of drip emitters were average discharge (Qavg %), discharge variation (Qvar), coefficient uniformity (CU %), coefficient of manufacture variation (CV), emission uniformity (EU %) and statistical uniformity (US %). The treatments were laid out in a randomized complete block design (RCBD) with four replicates. The result showed that the values of (CU%), (CV), (EU%), (US%) and percentage emitters clogging (Pclog %) were 97.9%, 0.38, 40.7%, 58.6%, 1.9% and 96.4%, 0.43, 52.1%, 57.7%, 1.8% and 96.4%, 0.6, 28.3%, 47.5%, 1.3% for regular gauge (RG), compensating pressure (CP) and non-compensating pressure (NCP) respectively. It is considered coefficient uniformity (CU %), was excellent and found to be within the acceptable range while discharge variation (Qvar %), emission uniformity (EU %), coefficient of manufacture variation (CV), and statistical uniformity (Us %) were found to be within the range of poor and unacceptable. Result also showed significant differences among types of emitters on plant height, applied water, yield and water productivity of eggplant. The highest yield was obtained non-compensating pressure (NCP) (13279 kg/ha) while the lowest yield was obtained by regular gauge (RG) (8180 kg/ha). The highest water productivity was obtained by regular gauge (RG) (7.7 kg/m<sup>3</sup>), while the lowest value was obtained by compensating pressure (CP) (4.8 kg/m<sup>3</sup>). The study recommends that the best type of emitter was non-compensating pressure (NCP), because it produced the highest yield of eggplant.

Keywords: Drip irrigation, hydraulic performance, emitter clogging, water productivity, uniformity

#### Introduction

Drip irrigation sometimes referred to as trickling irrigation, micro-irrigation, or low-volume irrigation, is the ideal technique since it offers a high degree of regularity. Compared to conventional irrigation systems, drip irrigation systems typically consume 30 to 50 percent less water since they supply (Almajeed and Alabas, 2013)<sup>[2]</sup>. In drip irrigation, dripper emitters deliver small, frequent doses of water to each plant individually. It has the highest application efficiency of any irrigation technique (Phocaides, 2001) <sup>[15]</sup>. When it comes to high-value cash crops like greenhouse plants, ornamentals, and fruit, drip irrigation technology is gaining popularity and playing a significant role in agricultural output (Pescod, 1992)<sup>[14]</sup>. The most effective and cost-effective form of irrigation for vegetable production is drip irrigation (Sharu and Abrazak, 2020)<sup>[16]</sup>. The Advantage of drip irrigation system include: less water, fertilizer and nutrients can be used with high efficiency, reduction in weed growth, reduced labor requirement, less soil erosion. While its disadvantage includes: clogging of drip holes, high initial investment requirement, soil salinity hazard and easy damage of drip lines (Gruban and Denton, 2004) [8]. At the plant, field, farm, system, and basin levels, water productivity can be examined. Its worth would fluctuate with the analysis's scale (Molden et al., 2003)<sup>[12]</sup>.

When calculating irrigation efficiency, water engineers traditionally ignored economic considerations and compared real evapo-transpiration (ET) to the total amount of water diverted for crop production (Kijne *et al.*, 2003)<sup>[10]</sup>.

Agriculture has a substantially lower economic value of water than other industries, including manufacturing (Xie and Walther, 1993)<sup>[19]</sup> (Barker *et al.*, 2003)<sup>[3]</sup>. Researchers were concerned with increasing the productivity of water use in agriculture in order to get the most production or value out of every unit of water used as a result of the growing physical shortage of water on the one hand, and the scarcity of economically accessible water due to increasing cost of production and supply of the resource on the other (Kijne *et al.*, 2003)<sup>[10]</sup>. However, little information is available on hydraulic performance of different types of emitters in Somalia. The main objective of this research work is to evaluate of hydraulic performance of three different emitters in drip irrigation systems for small vegetable farm in Gezira sate, Sudan.

### **Materials and Methods**

The experiment was carried out Agricultural Experiment farm owned by the University of Gezira Faculty of Agricultural Science, at latitude  $14^{\circ}21'$  N, longitude  $29^{\circ}33'$  E and altitude 405 m above mean sea level. The experimental site is clay, dark brown, deep cracking with very low permeability (Soil Survey Staff, 1999)<sup>[17]</sup>. The experiment started at the beginning of (fall) season during October 2021 up to the (Winter) season March 2022. The area of the experimental plot was 170 m<sup>2</sup> with dimensions of 17 m\*10 m. Four replications of a randomized complete block design were used to set up the experimental plot. Three treatments were used which were regular gauge (RG), compensating pressure (CP) and non-compensating pressure (NCP).

## Methods

## **Discharge of emitter**

Average discharge rate was measured using graduated measuring cylinder, catch cans and stopwatch. The model was lifted to work until one of the catch cans was filled stopped the watch and then the collected water in catch cans measured. To determine the average capacity in liters, the test was conducted three times. To calculate the discharge, divide the average volume by the passage of time.

q = V/t

Where: q = Discharge (L/h) V = Volume collected (ml) t = Time taken (hours)

## **Discharge variation (Qvar)**

Emitter flow variation (qvar) was calculated using the following equation:

Qvar = (Qmax - Qmin)/Qmax

#### Where

Qvar = Flow variation

q max = maximum emitter flow rate (L/h) q min = minimum emitter flow rate (L/h)

## Coefficient of uniformity (CU %)

According to the equation established by Christiansen (1942) <sup>[6]</sup>, the coefficient of uniformity was calculated as follows:

CU = 100 - (80\*Sd/Vavg)

#### Where

CU = Uniformity coefficient (%) Sd = Standard deviation of observation Vavg = Average volume collected.

## Coefficient of manufacture variation (CV %)

The Coefficient variation can be computed using the formula below (Burt and Styles, 200 Coefficient of manufacture variation (CV %). The Coefficient variation can be computed using the formula below (Burt and Styles, 2007) <sup>[5]</sup>.

CV% = 100 \* SD/q

### Where

CV = the coefficient of variation of emitter discharge. SD = standard deviation of emitter discharge. q = average discharge in the same lateral lines (L/h).

### **Emission uniformity (EU %)**

According to (Keller and Blaisner 1990) <sup>[21]</sup> the emission uniformity is defined as follows:

EU (%) = (qavg25%/q avg)\*100

#### Where

Qavg 25% = mean of the lowest 0.25 of emitter discharge. q avg = average discharge rate of all the emitters checked in the field (L/h).

### Statistical Uniformity (%)

The statistical uniformity was computed according to the following equation by (Bralts and Kesner, 1987)<sup>[4]</sup>.

Us = 100 (1 - Sq/q)

Where

Us = Statistical Uniformity (%)

Sq = Standard deviation of emitters discharge (l/h).

q = Discharge of emitters (l/h).

#### Percentage of Clogging emitters (Pclog %)

The following equation was used to calculate the percentage of clogged emitters Where

$$P_{c \log \%} = 100 \left[ \frac{Nes_{c \log}}{Nes_{total}} \right]$$

Pclog = Percentage of clogging emitters (%). Nesclog = Numbers of clogged emitters. Nestotal = total numbers of emitters.

#### Statistical analysis

Using an appropriate randomized complete block design analysis of variance MSTAT programme.

#### **Results and Discussions**

**Discharge (l/h):** The emitters discharges were measured and calculated and the Table 1 presents the findings. It's observed based on Table (1) that the average discharge rates of emitters were 1.8l/hr, 2.2 l/h and 3.7 l/h for Regular gauge (RG), compensating pressure (CP) and noncompensating pressure (NCP), respectively. The highest value was obtained by the non- compensating pressure emitter (3.7 1/h) while the lowest value was obtained by the regular gauge (1.8 1/h).

Table 1: Emitter discharge (l/h)

Emitter type	Q l/hr
RG	1.8
СР	2.2
NCP	3.7

#### **Discharge variation (Q var)**

The emitter variation discharge were measured and calculated and the results are displayed in Table (2). The mean measured discharge variations of emitters were 28.5, 31.7, and 33.8 for the regular gauge emitter (RG), the compensating pressure emitter (CP) and the non-compensating pressure (NCP), respectively. The highest mean value was obtained by the compensating pressure emitter (33.8) while the lowest value was obtained by the regular gauge emitter (28.5). According to the maximum drip irrigation standard of 20 to 30 for the discharge variation recommended by FAO (1984) the results obtained by the results from the other two types of emitters were generally unacceptable.

Table 2: Discharge variation of emitter's type (Qvar)

Emitter type	Means	Criteria
RG	28.5	20-30
Classification	Acceptable	Acceptable
СР	31.7	More than 30
Classification	Unacceptable	Unacceptable
NCP	33.8	More than 30
Classification	Unacceptable	Unacceptable

## Uniformity Coefficient (CU %)

Table (3) present the effect of the different three types of emitters on coefficient uniformity. The average coefficient of uniformity values of 97.9%, 96.4% and 96.4% were excellent for regular gauge (RG), compensating pressure (CP) and none compensating pressure emitter (NCP), respectively. The highest mean value was obtained by the regular gauge emitter (RG) (97.9%) while the lowest value was achieved by the non-compensating pressure emitter (NCP) (96.4%). This result agrees with (Kirnak *et al.* (2014)<sup>[9]</sup> who reported that the coefficient of uniformity Hydraulic design has an impact on drip irrigation system, although manufacture's variation. Bralts *et al.* (1987)<sup>[4]</sup> reported that the coefficient of uniformity greater than 90% is excellent.

Table 3: Coefficient uniformity of emitters type (CU %)

Emitter type	Means	Criteria
RG	97.9	Above 90%
Classification	Excellent	Excellent
СР	96.4	Above 90%
Classification	Excellent	Excellent
NCP	96.4	Above 90%
Classification	Excellent	Excellent

#### **Coefficient manufacture variation (CV %)**

Table (4) displays effect of the three types of emitters on coefficient of manufacture variation of drip irrigation system. The coefficients of manufacture variation of flow rates were acceptable. The coefficient of manufacture variation values was 0.38, 0.43 and 0.6 for the regular gauge emitters (RG), compensating pressure emitters (CP) and

none compensating pressure emitters (NCP), respectively. The highest mean value (unacceptable) was obtained by the non-compensating pressure emitters (0.6) while the lowest value (low) was achieved by the regular gauge emitters (0.38). Similar results were obtained by Alabas (2014) <sup>[11]</sup> and Soccol *et al.* (2002) <sup>[13]</sup> who found that the mean coefficient of variation was 0.28 for drip irrigation systems.

Table 4:	Coefficient	of manufacture	variation (	(CV)	)

Emitter type	Means	Criteria
RG	0.38	0.3-0.4
Classification	Low	Low
СР	0.43	More than 0.4
Classification	Unacceptable	Unacceptable
NCP	0.6	More than 0.4
Classification	Unacceptable	Unacceptable

#### **Emission uniformity (EU %)**

The emission uniformity was measured and calculated and the results are shown in Table (5). It's observed from the Table (5) that the average emission uniformity of emitters was 40.7%, 52.1 and 28.3 for regular gauge (RG), compensating pressure (CP) and non- compensating pressure (NCP), respectively. The highest value was obtained by the compensating pressure emitter (52.1%) while the lowest value was obtained by non-compensating pressure emitter (28.3%).

Table 5: Emission uniformity (EU %)

Emitter type	EU%	Criteria
RG	40.7	Less than 70%
Classification	Poor	Poor
СР	52.1	Less than 70%
Classification	Poor	Poor
NCP	28.3	Less than 70%
Classification	Poor	Poor

**Statistical uniformity (Us %):** The statistical uniformity were measured and calculated and the results are shown in Table (6). It's observed from the Table (6) that the average statistical uniformity of emitters were 58.6%, 57.7% and 47.5% for Regular gauge (RG), compensating pressure (CP) and non- compensating pressure (NCP), respectively. The highest value was obtained by the non-regular gauge emitter (58.6%) while the lowest value was obtained by the non-compensating pressure (47.5%). This result agrees with by Soccol *et al.* (2002) <sup>[13]</sup> who reported that the statistical uniformity values less than 60% is unacceptable.

Table 6: Statistical uniformity (Us %)

Emitter type	ter type Means Criteria	
RG	58.6	Less than 60%
Classification	Unacceptable	Unacceptable
СР	57.7	Less than 60%
Classification	Unacceptable	Unacceptable
NCP	47.5	Less than 60%
Classification	Unacceptable	Unacceptable

#### Percentage of emitter clogging (pclog %)

Table (7) shows the impact of various emitter types on the percentage of emitters clogging of the drip irrigation system. The percentage of emitters clogging values of 1.9%, 1.8% and 1.7% were obtained by the regular gauge emitter (RG), compensating pressure emitter (CP) and none compensating

pressure emitter (NCP), respectively. The highest mean value was obtained by the regular gauge emitter (1.9%) while the lowest value was obtained by non- compensating pressure emitter (1.7%).

 Table 7: Percentage Emitters Clogging (Pclog %)

Emitter type	Means
RG	1.9
СР	1.8
NCP	1.7

#### Wetted diameter (cm)

Table (8) shows the effect of hydraulic performance on wetted diameter of drip irrigation. The result obtained shows that the average wetted diameter of emitters was 8.9 cm, 8.8 cm, and 9.6 cm for Regular gauge (RG), compensating pressure (CP) and non-compensating pressure (NCP), respectively. The highest value was achieved by the non-compensating pressure emitter (9.6 cm) while the lowest value was obtained by the compensated pressure (8.8 cm).

Table 8: Effect of emitter's type on wetted diameter (	cm)	)
--------------------------------------------------------	-----	---

Emitter type	Wetted diameter (cm)	
RG	8.9	
СР	8.8	
NCP	9.6	

#### Applied water (m<sup>3</sup>/ha)

The findings showed that the differences were highly significant differences ( $p \le 0.01$ ) in applied water between treatments of drip irrigation system. The results of the applied water obtained by the regular gauge emitter (RG), compensating pressure emitter (CP) and non-compensating pressure emitter (NCP). were1172.5 m<sup>3</sup>/ha, 151s1.7 m<sup>3</sup>/ha and 2165.6 m<sup>3</sup>/ha<sup>-1</sup>, respectively. The significantly highest applied water was obtained by the none-compensating pressure emitter (2114.7 m<sup>3</sup>/ha), while the lowest was achieved by the regular gauge emitter (1122.2 m<sup>3</sup>/ha).

#### Water productivity (kg/m<sup>3</sup>)

The water productivity associated with the different emitter's types is presented in Table (9). The results showed that there were significant differences ( $p \le 0.05$ ) between the different types of emitters. The range for water productivity (kg/m<sup>3</sup>) for the emitter's type (RG, CP, NCP) was 7.75 kg/m<sup>3</sup>, 4.81 kg/m<sup>3</sup> and 6.41 kg/m<sup>3</sup>, respectively. The significantly highest water productivity was obtained by the emitter regular gauge pressure. (7.7516 kg/m<sup>3</sup>) while the lowest was achieved by the compensating pressure emitter (4.81 kg/m<sup>3</sup>).

Similar results were obtained by Yagoub (2018)  $^{[22]}$  who reported that water productivity under full irrigation treatment was 7.5 kg/m<sup>3</sup>.

### Yield (kg/ha)

The results indicate that there was a significant difference  $(p \le 0.05)$  between treatments under drip irrigation system. The yields obtained by the regular gauge emitter (RG), compensating pressure emitter (CP) and non-compensating pressure emitter (NCP) were 8627 kg/ha, 9313 kg/ha and 13477 kg/ha, respectively. The findings of the statistical study showed that were significant differences  $(p \le 0.05)$  in yield between the different irrigation treatments. The highest crop yield was obtained by the non-compensating pressure

emitter (13279 kg/ha), while the lowest yield was achieved by the regular gauge emitter (8180 kg/ha). There was a reduction in yield of 20, 29 and 44%, by the drip irrigation treatments compared to fully irrigated treatments. These results agree with the findings Karam *et al.*, (2009) <sup>[20]</sup> and Topcu *et al.*, (2007) <sup>[18]</sup>.

 Table 9: Effect of emitters' type on yield, applied water and water productivity

Treatment	AW(m3/ha)	WP(kg/m3)	Yield (kg/ha)
RG	1122.2 c	7.7516 a	8180 a
CP	1745.7 b	4.8138 b	8342 b
NCP	2114.7 a	6.4105 ab	13279 a
SE±	67	0.73	1255.9
CV	8.66	16.31	17.88
Sig. level	**	*	*

\* = means are significant at  $p \le 0.05$  level

\*\* = means are highly significant at  $p \le 0.01$  level

# Conclusion and Recommendation Conclusion

Evaluation of drip irrigation system performance is required periodically to ensure that the right emitter discharge is maintained. Results of this study on the hydraulic performance in three types of emitters were conducted and can be drawn as the following points: The average discharge varied from 1.8 to 3.7 l/hr. The values of hydraulic performance of drip irrigation system under three types of emitters, including: coefficient uniformity (CU %), was quite good and found to be within the acceptable range while discharge variation (Qvar %), emission uniformity (EU %), coefficient of manufacture variation (CV), and statistical uniformity (Us %) were found to be within the range of poor and unacceptable. Regular gauge (RG) is the best one for all parameters of hydraulic performance except on average discharge, emission uniformity and clogging percent. The highest yield of eggplant was obtained by noncompensating pressure (13279 kg/ha), while the highest water productivity was obtained by regular gauge (7.75 kg/m<sup>3</sup>).

#### Recommendation

Hydraulic performance of this result was recommended as the following: The best one emitter type is the regular gauge (RG) because it has the highest water productivity as compared to other emitters, non-compensating pressure emitters (NCP) and compensating pressure emitters (CP). It's still necessary to have more studies studies for better understanding of eggplant respond to drip irrigation.

#### Acknowledgment

The study supported by Gezira University and Faculty of Agricultural Science. The success of this study would not have been possible without the cooperation and readiness of the herd owners. All assistance and support were much appreciated.

#### References

- 1. Ahmed MYM. The Hydraulic Performance of Drip Irrigation System with Special Emphasis on the Effects of Deficit Irrigation on Eggplants (*Solanum Melongena* L.) Under Gezira Conditions; c2018.
- 2. Almajeed MA, Alabas A. Evaluation the Hydraulic Performance of Drip Irrigation System with Multi Cases Evaluation the Hydraulic Performance of Drip Irrigation System with Multi Cases Evaluation the

Hydraulic Performance of Drip Irrigation System with Multi Cases; c2013. http://creativecommons.

- Barker R, Dawe D, Inocencio A. Economics of water productivity in managing water for agriculture. In Water Productivity in Agriculture: Limits and Opportunity for Improvement Ed. JW Kijne, R Barker, D. Molden, CABI Publication and IWMI; c2003.
- 4. Bralts VF, Kesner CD. Drip irrigation field uniformity estimation. Transactions of the ASAE. 1987;26(5):1369-1374.
- Burt CM, Styles SW. Drip and Micro Irrigation Design and Management for Trees, Vines, and Field Crops. Practice plus Theory. 4<sup>th</sup> Edition. ISBN 978-0-9643634-4-1; c2007. p. 396.
- 6. Christiansen JE. Irrigation by sprinkler. Agricultural experiment station, University of California, Berkeley; c1942.
- 7. FAO. Localized Irrigation: Design, Installation, Operation and Evaluation. Irrigation and Drainage paper, No. 36, FAO, Rome; c1984.
- 8. Grubben GJH, Denton OA. Plant Resources of Tropical Africa 2, PROTA Foundation, Wageningen, Netherlands; c2004.
- 9. Kirnak H, Douan E, Demur S, Yalcin S. Determination of hydraulic performance of trickle irrigation emitters used in irrigation systems in the Harran Plain. Turk Journal of Agricultural. 2014;28(4):223-230.
- 10. Kijne JW, Barker R, Molden DJ. (Eds.) Water productivity in agriculture: Limits and opportunities for improvement. Cabi; c2003, p.1.
- 11. Mohamed A, Alabas AA. Evaluation the hydraulic performance of drip irrigation system with Multi case. Global journal of researchers in engineering general engineering. Version 1.0. publisher: Global Journals Inc. (USA), 2014, 13(2).
- 12. Molden D, Murray-Rust H, Sakthivadivel R, Makin I. A water-productivity framework for understanding and action. Water productivity in agriculture: Limits and opportunities for improvement. 2003;1:1-8.
- Soccol OJ, Ullmann MN, Frizzone JA. Performance analysis of trickle irrigation subunit installed in an apple orchard. Brazilian archives of biology and technology. An international Journal. 2002;45(4):625-530.
- 14. Pescod MB. Wastewater treatment and use in agriculture. Food and Agriculture Organization of the United Nations; c1992.
- 15. Phocaides A. FAO, Hand Book on pressurized irrigation techniques food and Agricultural Organization of The United Nations, Rome; c2001. p.11-94.
- Sharu EH, Ab Razak MS. Hydraulic performance and modeling of pressurized drip irrigation system. Water (Switzerland). 2020;12(8):2295. https://doi.org/10.3390/w12082295.
- 17. Soil survey staff. Soil survey manusl United state Dept.of Agriculture, Handbook No.18. Washington; c1999.
- Topcu S, Kirda C, Dasgan Y, Kaman H, Cetin M, Yazici A, *et al.* Yield response and N-fertilizer recovery of tomato grown under deficit irrigation. European Journal of Agronomy. 2007;26(1):64-70.
- 19. Xie Z, Walther JV. Quartz solubilities in NaCl solutions with and without wollastonite at elevated temperatures

and pressures. Geochimica et Cosmochimica Acta. 1993;57(9):194.

- 20. Karam F, Kabalan R, Breidi J, Rouphael Y, Oweis T. Yield and water-production functions of two durum wheat cultivars grown under different irrigation and nitrogen regimes. Agricultural water management. 2009;96(4):603-15.
- 21. Keller B. Chain complexes and stable categories. Manuscripta Mathematica. 1990;67(1):379-417.
- 22. Yu X, Bao X, Zhou C, Zhang L, Yagoub AE, Yang H, *et al.* Ultrasound-ionic liquid enhanced enzymatic and acid hydrolysis of biomass cellulose. Ultrasonics Sonochemistry. 2018;41:410-418.